






TOTAL MARKETING SERVICES

Bitumen Operations

Head Office: 562 avenue du Parc de l'île 92029 Nanterre Cedex – France Tel +33 (0)1 41 35 40 00 www.bitumen.total.com

Share capital €324.158.696
Trade & Companies Register Nanterre
www.total.com



Styrelf ECO2: For warm-mix asphalt, ready to use Styrelf BC: Suitable for recycling Styrelf GP: Specially designed for race tracks

FOR EACH SPECIFIC WORKSITE, TOTAL CAN OFFER THE IDEAL TECHNICAL SOLUTION



A COMPLETE RANGE FOR ALL ROADS

The Styrelf® range meets all market demands for secondary and main road networks as well as motorways.



LOGISTICS MADE EASIER

- Perfect stability during storage

EXCELLENT DURABILITY

- Outstanding elasticityReduced thermal susceptibility
- Increased resistance to aging

A HIGH PERFORMANCE SOME AN ASPHALT WITH EXCEPTIONAL PROPERTIES

RESISTANCE TO THERMAL SURFACE CRACKING

- Excellent performance at low temperatures
- High resistance of binder to cracking

RESISTANCE TO FATIGUE


Highly superior to conventional road grades

RESISTANCE TO RUTTING

- Excellent performance at high temperaturesSignificant elastic recovery


RESISTANCE TO FRETTING

- High level of cohesion



GILLES GAUTHIER, Technical Manager for Total Bitumen

AN EVER-GROWING NUMBER OF PRODUCTS TO OFFER A RANGE ADAPTED TO ALL YOUR NEEDS



- AP: Improved adhesion of the binder to aggregates that are difficult to coat
- ECO²: Styrelf performance at low temperatures
- TR:Lower viscosity for hard and/or highly modified grades





THE READY TO USE
TECHNICAL SOLUTION FOR
WARM-MIX ASPHALT





SIMILAR PERFORMANCE

TO STYRELF FOR HOT-MIX ASPHALT

- In terms of mechanical and durability performance



READY TO USE

- No modifications needed to asphalt mixing plant equipment
- No investment necessary to use warm-mix technology



LOWER ASPHALT MIX PRODUCTION

AND APPLICATION TEMPERATURES OF 40°C

- Energy-saving
- Reduced CO₂ emissions




IMPROVED COMFORT


AND VISIBILITY OF ON-SITE TEAMS

- Less fumes

ALL BY SIMPLY REDUCING THE TEMPERATURE!



Energy consumption



Emission of CO₂

at the coating plant

USED FOR WEARING COURSES AND BASE COURSES
COMPATIBLE WITH INCORPORATION OF RECYCLED ASPHALT PAVEMENT
BACK UP TO TRAFFIC QUICKER



TOTAL MARKETING SERVICES Bitumen Operations

Head Office: 562 avenue du Parc de l'île - 92029 Nanterre Cedex - France Tel +33 (0)1 41 35 40 00 www.bitumen.total.com share capital €324.158.696 Trade & Companies Register Nanterre www.total.com



STYRELF ECO² is labelled Total Ecosolutions. To find out more, visit our website at www.total.com/total-ecosolutions



THE REFERENCE FOR PARKING OR STORAGE AREAS SUBJECT TO **HYDROCARBONS DAMAGE**



THE SOLUTION FOR HEAVY DUTY AREAS




- Parking facilities and taxiways in airports
- Container terminals
- Service station traffic and parking areas

IMPROVED RESISTANCE


- Toll booths
- Roundabouts, HGV parking areas and bus stops
- Traffic lanes in plants and warehouses

EXCEPTIONAL PERFORMANCE





EXCELLENT RESISTANCE TO RUTTING




Testing conducted at 30,000 cycles in line with standard EN 12697-22




EASIER TO HANDLE THANKS TO A LOWER VISCOSITY

Iso-viscosity temperature (200mPa.s-1) close to the one of a bitumen 20/30 $\,$





EXCELLENT RESISTANCE TO FRETTING



Head Office: 562 avenue du Parc de l'île - 92029 Nanterre Cedex - France
Tel +33 (0)1 41 35 40 00 www.bitumen.total.com
Share capital €324.158.696 Trade & Companies Register Nanterre www.total.com





THE TECHNICAL SOLUTION DEDICATED TO **RECYCLING** HEAVY DUTY ROADS



THE ONLY MODIFIED
BINDER ON THE MARKET
FORMULATED ESPECIALLY FOR
RECYCLING



THE SOLUTION FOR HIGH-TRAFFIC WEARING COURSES INCORPORATING RECYCLING ASPHALT PAVEMENT (RAP)

- For all asphalt types (high modulus, semi-coarse, very thin)
- For percentages of RAP between 10 and 40%
- For varying degrees of RAP oxidation



AVAILABLE IN 3 GRADES:

Modified Styrelf RC bitumen are available in 3 grades with differing RAP percentages and properties*.

Degree of RAP oxidation	Percentage of RAP	
	15-25%	30-40%
Low	Styrelf 40 RC	Styrelf 60 RC
Average	Styrelf 60 RC	Styrelf 60 RC
High	Styrelf 60 RC	Styrelf 80 RC

*Our Technical Services are on hand to help you get the grade you need for your worksite specifications.



SUSTAINABLE SUPPORT FOR ROAD RECYCLING

Head Office: 562 avenue du Parc de l'île - 92029 Nanterre Cedex - France Tel +33 (0)1 41 35 40 00 www.bitumen.total.com
Share capital €324.158.6969 Trade & Companies Register Nanterre www.total.com





THE WOLDWIDE REFERENCE FOR VERY HIGH PERFORMANCE ROADS CIRCUITS, TEST TRACKS...




A WORLDWIDE REFERENCE






BETTER DURABILITY THAN CONVENTIONAL BITUMEN

30% higher resistance to fretting compared to bitumen 35/50



Styrelf GP keeps its low-temperature properties year after year on the road.



Total test on turntable at 25°C




Head Office: 562 avenue du Parc de l'île - 92029 Nanterre Cedex - France Tel +33 (0)1 41 35 40 00 www.bitumen.total.com Share capital €324.158.696 Trade & Companies Register Nanterre www.total.com





THE TECHNICAL SOLUTION WITH ADDITIVES FOR IMPROVED ADHESION








IMPROVED PERFORMANCE FOR ALL AGGREGATES, EVEN THOSE THAT ARE DIFFICULT TO COAT

- Can meet water resistance criteria for asphalt required by worksite specifications
- Maintains asphalt water resistance over time

PASSIVE ADHESION TEST EN 15626



BETTER ADHESION OF STYRELF AP TO AGGREGATES



IMPROVE WATER RESISTANCE OF ASPHALT



NO ADDITIONAL HANDLING OF ADDITIVES IN THE ASPHALT MIXING PLANT



NO MODIFICATIONS TO INDUSTRIAL FACILITIES THANKS TO THE READY-TO-USE BINDER

FOR THE LONG-TERM PROTECTION OF ROADS AGAINST WATER

TOTAL MARKETING SERVICES Bitumen Operations


Head Office: 562 avenue du Parc de l'île - 92029 Nanterre Cedex - France Tel +33 (0)1 41 35 40 00 www.bitumen.total.com Share capital €324.158.696 Trade & Companies Register Nanterre www.total.com






THE TECHNICAL SOLUTION THAT FACILITATES THE USE OF **HIGH VISCOSITY** BINDERS ON INDUSTRIAL SITES





TO APPLICATIONS REQUIRING HIGHLY MODIFIED BINDERS IN AREAS WHERE APPLICATION IS DIFFICULT





NO MODIFICATIONS
TO INDUSTRIAL FACILITIES



ENERGY SAVINGS THANKS TO LOWER TEMPERATURES OF UP TO 15°C

TO MANUFACTURE DURARUE ASDIJAUT FASILY

TOTAL MARKETING SERVICES Bitumen Operations

Head Office: 562 avenue du Parc de l'île - 92029 Nanterre Cedex - France Tel +33 (0)1 41 35 40 00 www.bitumen.total.com
Share capital €324.158.696Trade & Companies Register Nanterre www.total.com

